



Product Service

CERTIFICATE

No. Z2 10 03 68988 006

Holder of Certificate: Jiangyin Jetion Science and Technology Co., Ltd.No. 1011, Zhencheng Rd.,
Shengang Industrial District
214443 Jiangyin
PEOPLE'S REPUBLIC OF CHINA**Certification Mark:****Product:****Crystalline Silicon Terrestrial Photovoltaic (PV) Modules
Mono-Crystalline Silicon Photovoltaic Module**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.:

704060940501-02

Date, 2010-03-04


(Jianhui Wang)

Page 1 of 2





Product Service

CERTIFICATE**No. Z2 10 03 68988 006****Model(s):**

JT250(51)S1580x1069, JT245(50)S1580x1069, JT185(36)S1580x808, JT240(50)S1580x1069, JT235(50)S1580x1069, JT180(36)S1580x808, JT230(49)S1580x1069, JT225(49)S1580x1069, JT175(35)S1580x808, JT220(49)S1580x1069, JT210(49)S1580x1069, JT170(35)S1580x808, JT200(49)S1580x1069, JT225(45)S1455x1069, JT165(34)S1580x808, JT220(45)S1455x1069, JT215(45)S1455x1069, JT160(34)S1580x808, JT210(45)S1455x1069, JT205(45)S1455x1069, JT155(34)S1580x808, JT200(45)S1455x1069, JT190(36)S1580x808, JT090(19)S1195x541, JT085(19)S1195x541, JT080(18)S1195x541, JT075(18)S1195x541, JT060G, JT055G, JT050G, JT045G, JT040G, WJ60M, WJ55M, WJ50M, WJ45M, WJ40M, JT045F, JT040F, JT035F, JT030H, JT025H, JT020H

Parameters:

Rated Output Power at STC:

250W [JT250(51)S1580x1069]; 245W [JT245(50)S1580x1069];
 240W [JT240(50)S1580x1069]; 235W [JT235(50)S1580x1069];
 230W [JT230(49)S1580x1069]; 215W [JT215(45)S1455x1069];
 225W [JT225(49)S1580x1069, JT225(45)S1455x1069];
 220W [JT220(49)S1580x1069, JT220(45)S1455x1069];
 210W [JT210(49)S1580x1069, JT210(45)S1455x1069];
 200W [JT200(49)S1580x1069, JT200(45)S1455x1069];
 205W [JT205(45)S1455x1069];
 190W [JT190(36)S1580x808]; 185W [JT185(36)S1580x808];
 180W [JT180(36)S1580x808]; 175W [JT175(35)S1580x808];
 170W [JT170(35)S1580x808]; 165W [JT165(34)S1580x808];
 160W [JT160(34)S1580x808]; 155W [JT155(34)S1580x808];
 90W [JT090(19)S1195x541]; 85W [JT085(19)S1195x541];
 80W [JT080(18)S1195x541]; 75W [JT075(18)S1195x541];
 60W [JT060G, WJ60M]; 55W [JT055G, WJ55M];
 50W [JT050G, WJ50M]; 45W [JT045G, WJ45M, JT045F];
 40W [JT040G, WJ40M, JT040F]; 35W [JT035F];
 30W [JT030H] 25W [JT025H]; 20W [JT020H]

Construction:	Framed, with Junction box, Cable and Connectors.
Application Class:	Class A
Maximum System Voltage:	1000 V DC
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute No. 10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P. R. China

Tested according to:

IEC 61215:2005
 EN 61215:2005
 IEC 61730-1:2004
 EN 61730-1:2007
 IEC 61730-2:2004
 EN 61730-2:2007

Production Facility(ies):

68988

Page 2 of 2



Product Service

Attestation of Conformity

No. N8 10 03 68988 005

Holder of Certificate: Jiangyin Jetion Science and Technology Co., Ltd.No. 1011, Zhencheng Rd.,
Shengang Industrial District
214443 Jiangyin
PEOPLE'S REPUBLIC OF CHINA**Product: Crystalline Silicon Terrestrial Photovoltaic (PV) Modules
Mono-Crystalline Silicon Photovoltaic Module**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2006/95/EC relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 704060940501-02

Date, 2010-03-04

(Jianhui Wang)



After preparation of the necessary technical documentation as well as the EC conformity declaration the required CE marking can be affixed on the product. Other relevant directives have to be observed.

Page 1 of 2



Product Service

Attestation of Conformity**No. N8 10 03 68988 005****Model(s):**

JT250(51)S1580x1069, JT245(50)S1580x1069, JT185(36)S1580x808,
 JT240(50)S1580x1069, JT235(50)S1580x1069, JT180(36)S1580x808,
 JT230(49)S1580x1069, JT225(49)S1580x1069, JT175(35)S1580x808,
 JT220(49)S1580x1069, JT210(49)S1580x1069, JT170(35)S1580x808,
 JT200(49)S1580x1069, JT225(45)S1455x1069, JT165(34)S1580x808,
 JT220(45)S1455x1069, JT215(45)S1455x1069, JT160(34)S1580x808
 JT210(45)S1455x1069, JT205(45)S1455x1069, JT155(34)S1580x808
 JT200(45)S1455x1069, JT190(36)S1580x808, JT090(19)S1195x541,
 JT085(19)S1195x541, JT080(18)S1195x541, JT075(18)S1195x541,
 JT060G, JT055G, JT050G, JT045G, JT040G, WJ60M, WJ55M, WJ50M,
 WJ45M, WJ40M, JT045F, JT040F, JT035F, JT030H, JT025H, JT020H

Parameters:

Rated Output Power at STC:

250W [JT250(51)S1580x1069]; 245W [JT245(50)S1580x1069];
 240W [JT240(50)S1580x1069]; 235W [JT235(50)S1580x1069];
 230W [JT230(49)S1580x1069]; 215W [JT215(45)S1455x1069];
 225W [JT225(49)S1580x1069, JT225(45)S1455x1069];
 220W [JT220(49)S1580x1069, JT220(45)S1455x1069];
 210W [JT210(49)S1580x1069, JT210(45)S1455x1069];
 200W [JT200(49)S1580x1069, JT200(45)S1455x1069];
 205W [JT205(45)S1455x1069];
 190W [JT190(36)S1580x808]; 185W [JT185(36)S1580x808];
 180W [JT180(36)S1580x808]; 175W [JT175(35)S1580x808];
 170W [JT170(35)S1580x808]; 165W [JT165(34)S1580x808];
 160W [JT160(34)S1580x808]; 155W [JT155(34)S1580x808];
 90W [JT090(19)S1195x541]; 85W [JT085(19)S1195x541];
 80W [JT080(18)S1195x541]; 75W [JT075(18)S1195x541];
 60W [JT060G, WJ60M]; 55W [JT055G, WJ55M];
 50W [JT050G, WJ50M]; 45W [JT045G, WJ45M, JT045F];
 40W [JT040G, WJ40M, JT040F]; 35W [JT035F];
 30W [JT030H] 25W [JT025H]; 20W [JT020H]

Construction:	Framed, with Junction box, Cable and Connectors.
Application Class:	Class A
Maximum System Voltage:	1000 V DC
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute No. 10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P. R. China

**Tested
according to:**

EN 61730-1:2007
 EN 61730-2:2007

Page 2 of 2